

## 375°F / 190°C: Abrasion & Wear Resistant Nylon Protection Sleeve Scuff-Sleeve™: for Hose, Wire and Cable



- Heavy Wall version of S-N-APS-SD sleeve.
- Abrasion & wear resistant sleeve for hoses, wires and cables.
- Conforms to Commercial Item Description (CID) A-A-59301 and specification MIL-C-572.
- Tight weave and smooth surface resists abrasive wear.
- Nylon 6 provides excellent UV protection.
- Easily cut to length or cut with heat knife.
- Useable -60°F to +375°F.

Helps to organize and bundle hoses and cables, while proving heat resistance to a maximum of 375°F continuous duty, and provides excellent abrasion, scuff and wear resistance.

### Scuff-Sleeve™ Nylon Abrasion & Wear Protection Sleeve – Heavy Wall

#### A-A-59301 and MIL-C-572

Part Number	ID Size			Wall Thickness	Spool Feet / Spool Price
	inch	mm	-dash		
S-N-APS-SDHD-M005-03	3/16	4.76	-03	.029	500 / \$ 548.25
S-N-APS-SDHD-M006-04	1/4	6.35	-04	.030	500 / \$ 729.37
S-N-APS-SDHD-M008-05	5/16	7.93	-05	.030	500 / \$ 911.87
S-N-APS-SDHD-M010-06	3/8	9.52	-06	.032	250 / \$ 533.56
S-N-APS-SDHD-M011-07	7/16	11.12	-07	.032	250 / \$ 577.12
S-N-APS-SDHD-M013-08	1/2	12.7	-08	.034	250 / \$ 617.94
S-N-APS-SDHD-M016-10	5/8	15.87	-10	.038	150 = \$ 613.54 / 250 = \$ 1022.56
S-N-APS-SDHD-M019-12	3/4	19.05	-12	.042	150 = \$ 742.46 / 250 = \$ 1237.44
S-N-APS-SDHD-M022-14	7/8	22.22	-14	.042	100 = \$ 661.05 / 250 = \$ 1652.63
S-N-APS-SDHD-M025-16	1	25.4	-16	.047	100 = \$ 815.85 / 250 = \$ 2039.63

Other lengths may be available: please enquire.

This sleeve is non-expandable – please measure your application carefully.