

375°F / 190°C: Abrasion Protection Sleeve Scuff-Sleeve™: for Hose, Wire and Cable



- Abrasion resistance sleeve for hoses, wires and cables.
- Exceeds the new “Line of Sight” operator protection regulations EN982 ISO norm 833 EN414 for hose blowout.
- Ultra tight weave provides leak containment.
- Tight weave and smooth surface resists abrasive wear.
- Less bulky than older cordura sleeves.
- Nylon 6 provides excellent UV protection.
- MSHA approved.
- Exceeds ISO 6945 abrasion standard and ISO 8031 conductivity standard.
- Easily cut to length or cut with heat knife.
- Useable -60°F to +375°F.
- Also available as a Sleeve with Velcro for easy retrofit onto wires, cables or hoses that are already in place.

Helps to organize and bundle hoses and cables, while proving heat resistance to a maximum of 375°F continuous duty, and provides excellent abrasion, scuff and wear resistance.

Scuff-Sleeve™ Nylon Abrasion Protection Sleeve				
Part Number	ID Size			Price per Foot / Metre
	inch	mm	-dash	
S-N-APS-M017-11	0.67	17	-11	\$ 1.52 / \$ 4.98
S-N-APS-M020-13	0.79	20	-13	\$ 1.57 / \$ 5.15
S-N-APS-M023-15	0.91	23	-15	\$ 1.62 / \$ 5.31
S-N-APS-M024-16	0.96	24	-16	\$ 1.79 / \$ 5.87
S-N-APS-M026-17	1.06	26	-17	\$ 1.88 / \$ 6.17
S-N-APS-M030-20	1.22	30	-20	\$ 1.97 / \$ 6.46
S-N-APS-M036-23	1.42	36	-23	\$ 2.13 / \$ 6.99
S-N-APS-M039-26	1.57	39	-26	\$ 2.28 / \$ 7.48
S-N-APS-M043-28	1.73	43	-28	\$ 2.43 / \$ 7.97
S-N-APS-M047-30	1.85	47	-30	\$ 2.74 / \$ 8.98
S-N-APS-M055-35	2.17	55	-35	\$ 3.16 / \$ 10.37
S-N-APS-M059-38	2.36	59	-38	\$ 3.43 / \$ 11.25
S-N-APS-M072-46	2.87	72	-46	\$ 4.67 / \$ 15.32
S-N-APS-M074-48	2.95	74	-48	\$ 5.67 / \$ 18.60
S-N-APS-M092-59	3.66	92	-59	\$ 5.80 / \$ 19.03
S-N-APS-M125-80	4.94	125	-80	\$ 9.77 / \$ 32.05

Sold in standard lengths of 75, 150 and 300 feet.

Other lengths may be available: please enquire.

This sleeve is non-expandable – please measure your application carefully.